

XB1564



15GA Finish Nailer

Applications

Cabinet Assembly, Door & Window Manufacturing, Drawer Assembly, Finish Carpentry, Hardwood Flooring, Trim Molding

Specifications

Fastener Length	1" - 2-1/2"
Magazine Capacity	100
Actuation Mode	Full Sequential Actuation
Dimensions	10" x 3" x 10-1/2"
Weight	4.4 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	3/8"
Air Consumption per Cycle @ 90 PSI	0.042 SCF
Noise Power Emissions per EN12549 LwA,1s	106.5 dBA
Noise Pressure Emissions per EN12549 LpA,1s	105.0 dBA
Vibration Emissions per ISO-8662-11	3.39 m/s ²
Vibration Value Uncertainty per ISO-8662-11	1.50 m/s ²

Features

360° Adjustable Exhaust, Adjustable Depth Control, Ergonomic Rubber Grip, No Mar Tip, Quick Clear Nose, Rear Load Aluminum Magazine

Includes

Allen Wrenches, Contact Actuation Trigger, Safety Glasses, Tool Case, Tool Oil

Accessory

Air Filter (P-97454)



For Best Results Use Spotnails® Collated Fasteners

15GA Brads

STOCK No.	LENGTH	M/Bx	Bx/Cs
Galvanized			
1512PG	1-1/2"	2.5	10
1514PG	1-3/4"	2.5	10
1516PG	2"	2.5	10
1520PG-15M	2-1/2"	2.5	6



Jan. 2022