



NOTES:

1. INLET: 5/16" BARB
2. OUTLETS: 5/16" BARB W/ SHUTOFF
3. GAUGES: 60# (4 EA)
4. SAFETY BLOW-OFF: 60 ± 5 PSI
5. WORKING PRESSURE: 0-50 PSI
6. POLY BONNETS WITH ADJ GOLD CAPS

MATERIAL	DRAWN	NAME	DATE
	JPK	JPK	08/02/11
FINISH	ENG APPR.		
<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.</p>			
<p>DIMENSIONS ARE IN INCHES</p> <p>TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005</p>			



<p>TITLE: REG SEC BEER WM,4P4P, 5/16B IN, 5/16B SHUTOFF, POLY GOLD, 4 X "Y's", 21" PNL</p>		
SIZE	DWG. NO.	REV
A	T1694STWMK_SALES	E
SCALE: 1:3	DO NOT SCALE DRAWING	SHEET 1 OF 1