



**NOTES:**

1. INLET: NITROGEN TANK FITTING
2. OUTLET: SHUTOFF W/CV & 5/16" BARB
3. GAUGE: 60# REG. GAUGE  
3000# TANK GAUGE
4. SAFETY BLOW-OFF: 60 ± 5 PSI
5. WORKING PRESSURE 0-50 PSI
6. ZINC BONNET, BLACK

MATERIAL	NAME	DATE
	DRAWN	JRS 10/12/10
FINISH	ENG APPR.	
<p><b>PROPRIETARY AND CONFIDENTIAL</b></p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.</p>		
<p>DIMENSIONS ARE IN INCHES</p> <p>TOLERANCES:          FRACTIONAL ± 1/64          ANGULAR: MACH ± 1/2°          BEND ±          TWO PLACE DECIMAL ± 0.015          THREE PLACE DECIMAL ± 0.005</p>		

**TAPRITE**  
2348 NORTHWESTERN DR. SAN ANTONIO, TX 78238

**TITLE:**  
**REG PRI BEER NI, 60#, TNK  
 FTG, 5/16B-CV SHUTOFF,  
 3000#, BLACK BONNET**

SIZE	DWG. NO.	REV
<b>A</b>	<b>742N_SALES</b>	<b>A</b>

SCALE: 1:2      DO NOT SCALE DRAWING      SHEET 1 OF 1