

# T1S6825S



## 18GA Medium Crown String Feed Stapler

### Applications

Insulation Installation, Siding

### Specifications

Fastener Crown	3/8"
Fastener Length	3/8" - 1"
Magazine Capacity	168
Actuation Mode	Selective Actuation
Dimensions	9-1/2" x 2-1/2" x 8-1/4"
Weight	2.75 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	1/4"
Air Consumption per Cycle @ 90 PSI	0.016 SCF
Noise Power Emissions per EN12549 LwA,1s	96.6 dBA
Noise Pressure Emissions per EN12549 LpA,1s	86.9 dBA
Vibration Value Less than 2.5 m/s <sup>2</sup> per ISO-8662-11	
Vibration Value Uncertainty per ISO-8662-11	0.73 m/s <sup>2</sup>

### Features

360° Adjustable Exhaust, Adjustable Depth Control, Ergonomic Rubber Grip, Quick Clear Nose, Top Load Aluminum Magazine

### Includes

Allen Wrenches, Safety Glasses, Tool Case, Tool Oil

### Accessory

Full Sequential Actuation Trigger (AS-21040)



### For Best Results, Use Spotnails® Collated Fasteners

18GA 3/8" Medium Crown Staples

(Similar to Senco® M / Duo-Fast® W1800)

Stock No.	LENGTH	M/Bx	Bx/Cs
-----------	--------	------	-------

#### Galvanized

6803PG-50M	3/8"	5	10
6804PG-50M	1/2"	5	10
6805PG-50M	5/8"	5	10
6806PG-50M	3/4"	5	10
6807PG-50M	7/8"	5	10
6808PG-50M	1"	5	10