EKXTREME: PARKER

UNGLAZED PORCELAIN







Nominal Sizes and Colours

Available in: 24x48 Natural, 48x106 Natural





Parker Silver



Parker Smoke



Parker Anthracite



Special Order by Full Boxes Only: 24x24, 36x36, 48x48 Natural; 48x48 Antislip, 24x24, 24x48 20mm thickness; 2x2 Mosaic Natural; 3x48, 3x36, 3x24 Natural Bullnose

Recommended applications

necommenaea appi		
Residential	Bath / Shower	W Wall
Light commercial: all colours except Anthracite	Fireplace	Floor
Indoor		

Characteristics of	tile	
Low maintenance	Fade resistant	Resistant to fungus
Stain resistant	Eco-friendly	Odour resistant
Hypoallergenic		

Technical specifications

•			
Pattern Repeat	24x48: 15 48x106: 3	MOHS	n/a
Abrasion resistance	<175 mm ³	Tile thickness	24x48: 9 mm 48x106: 6 mm
Dynamic Coefficient of Friction	0.55	Chemical Resistance	Min class B
Frost Resistance	Yes	Variation	V1 V2 V3 V4
Water Absorption	≤ 0.5%		Moderate



Special instructions

■ Shade variations between tiles is characteristic. Colour may vary from sample.





