

DSP103020



Pneumatic Carton Closing Plier Stapler

Applications

Carton Closing, Fastening Corrugated Packaging, Packaging

Specifications

Fastener Crown	1/2"
Fastener Length	3/8" - 5/8"
Magazine Capacity	102
Actuation Mode	Trigger Actuation
Dimensions	14" x 2" x 10-1/4"
Weight	5 lbs
Operating Pressure	36 - 55 PSI
Air Inlet NPT	1/4"
Air Consumption per Cycle @ 50 PSI	0.005 SCF
Noise Power Emissions per EN12549 LwA,1s	94.0 dBA
Noise Pressure Emissions per EN12549 LpA,1s	86.0 dBA
Vibration Value Less than 2.5 m/s ² per ISO-8662-11	
Vibration Value Uncertainty per ISO-8662-11	0.08 m/s ²

Features

Heavy Duty, Industrial Strength, Side Exhaust, Top Load Steel Magazine

Includes

Air Fitting, Allen Wrenches, Tool Ring Hanger, Tool Oil

Accessories

Anvils (B, CL, CR, DL,DR), Compact Pressure Regulator 50 PSI Available (AS-97412), Remote Valve (AS-97420), Remote Valve with Foot Pedal (AS-97419)



For Best Results, Use Spotnails® Collated Fasteners

1/2" Crown Fine Wire Staples

(Similar to Bostitch® SB103020)

STOCK No.	LENGTH	M/Bx	Bx/Cs
Galvanized, Chisel Point			
91206	3/8"	2.5	20
91208	1/2"	2.5	20
91210	5/8"	2.5	20

RELIABILITY
Provin

Jan. 2022

Division of Peace Industries, LTD.

P: 800-873-2239 / 847-259-1620 | F: 888-369-2588 | customerservice@spotnails.com
SPOTNAILS.BIZ | SPOTNAILS.COM | RELIABILITYPROVIN.COM