

X1T8664



T-Nailer

Application

Fastening Tack Strips to Concrete

Specifications

| | |
|---|---------------------------|
| Diameter | .086 |
| Fastener Length | 5/8" - 2-1/2" |
| Magazine Capacity | 100 |
| Actuation Mode | Full Sequential Actuation |
| Dimensions | 14-1/4" x 3-1/2" x 10" |
| Weight | 4.55 lbs |
| Operating Pressure | 80-110 PSI |
| Air Inlet NPT | 3/8" |
| Air Consumption per Cycle @ 90 PSI | 0.042 SCF |
| Noise Power Emissions per EN12549 LwA,1s | 106.5 dBA |
| Noise Pressure Emissions per EN12549 LpA,1s | 105.0 dBA |
| Vibration Emissions per ISO-8662-11 | 3.39 m/s ² |
| Vibration Value Uncertainty per ISO-8662-11 | 1.50 m/s ² |

Features

360° Adjustable Exhaust, Adjustable Depth Control, Ergonomic Rubber Grip, Side and Top Load Steel Magazine

Includes

Allen Wrenches, Contact Actuation Trigger, Safety Glasses, Tool Case, Tool Oil

Accessories

Air Filter (P-97454), Walking Stick Attachment (AS-99105)



**For Best Results, Use
Spotnails® Collated Fasteners
.086 T-Nails**

| STOCK No. | LENGTH | M/Bx | Bx/Cs |
|----------------------------|--------|------|-------|
| Hardened Galvanized | | | |
| T08611H | 11/16" | 2.0 | 10 |

RELIABILITY
Provin

Jan. 2022

Division of Peace Industries, LTD.

P: 800-873-2239 / 847-259-1620 | F: 888-369-2588 | customerservice@spotnails.com
SPOTNAILS.BIZ | SPOTNAILS.COM | RELIABILITYPROVIN.COM